













» Technische Daten – Terrassenmarkisen

Modell	Kassettenmarkisen					Offene Gelenkarmmarkisen		
	360	330	230	300	301	100	101	186
 Breite minimal (cm)	195	188	188	185	180	150	180	200
 Breite maximal (cm)	650	700	700	550	400	600	500	600
 Breite maximal 2-wellig (cm)	1200	1200	1200	–	–	1200	–	1300
 Breite maximal 3-wellig (cm)	–	1800	1800	–	–	–	–	1900
 Kopplung mehrerer Anlagen	+	+	+	–	–	+	–	+
 Ausfall maximal (cm)	350	400	400	300	250	350	250	675
 Volant	+	+	+	+	–	+	+	+
 Variovolant	–	+	+	–	–	–	–	–
 Schutzdach/-kasten	✓	✓	✓	✓	✓	+	–	+
 Wandmontage	•	•	•	•	•	•	•	•
 Deckenmontage	•	•	•	•	•	•	•	–
 Dachsparrenmontage	•	•	•	•	•	•	–	–

Modell	Kassettenmarkisen					Offene Gelenkarmmarkisen		
	360	330	230	300	301	100	101	186
 Neigungsverstellung	0° – 45°	0° – 45°	0° – 45°	0° – 55° * ²	5° – 60°	5° – 40°	5° – 60°	* ¹
 Kurbelantrieb	✓	✓	✓	✓	✓	✓	✓	–
 Motorisierung	+	+	+	+	+	+	+	✓
 Funksteuerung	+	+	+	+	+	+	+	+
 Beleuchtung	+	+	+	+	+	+	+	+
 Wärmestrahler	+	+	+	+	+	+	+	+
 RAL - Sonderfarben	+	+	+	+	–	+	–	+

- ✓ Standard
- + Optional
- Möglich
- Nicht möglich

*¹ = errechnet sich aus der verfügbaren Höhe und dem Ausfall
 *² = bei Deckenmontage 8-63°